

## TO-92 Plastic-Encapsulate Transistors


### 2SD879 TRANSISTOR (NPN)

#### FEATURES

- In Applications Where Two NiCd Batteries are Used to provide 2.4V, two 2SD879s are used.
- The charge time is approximately 1 second faster Than that of germanium transistors.
- Less power dissipation because of low Collector-to-Emitter Voltage  $V_{CE(sat)}$ , permitting more flashes of light to be emitted.
- Small package and large allowable collector dissipation (TO-92,  $P_C=750mW$ ).
- Large current capacity and highly resistant to break-down.
- Excellent linearity of  $h_{FE}$  in the region from low current to high current. Power amplifier applications

#### TO-92

1. EMITTER
2. COLLECTOR
3. BASE



#### MAXIMUM RATINGS ( $T_a=25^{\circ}C$ unless otherwise noted)



Symbol	Parameter	Value	Unit
$V_{CBO}$	Collector-Base Voltage	30	V
$V_{CEO}$	Collector-Emitter Voltage	10	V
$V_{CEX}$		20	V
$V_{EBO}$	Emitter-Base Voltage	6	V
$I_C$	Collector Current –Continuous	3	A
$P_C$	Collector Power Dissipation	750	mW
$T_J$	Junction Temperature	150	$^{\circ}C$
$T_{stg}$	Storage Temperature	-55-150	$^{\circ}C$

#### ELECTRICAL CHARACTERISTICS ( $T_a=25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=10\mu A, I_E=0$	30			V
Collector-emitter breakdown voltage	$V_{(BR)CEX}$	$I_C=1mA, V_{BE}=3V$	20			V
	$V_{(BR)CEO}$	$I_C=10mA, I_B=0$	10			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=10\mu A, I_C=0$	6			V
Collector cut-off current	$I_{CBO}$	$V_{CB}=20V, I_E=0$			1	$\mu A$
Emitter cut-off current	$I_{EBO}$	$V_{EB}=4V, I_C=0$			1	$\mu A$
DC current gain	$h_{FE}^*$	$V_{CE}=2V, I_C=3A$	140			
Collector-emitter saturation voltage	$V_{CE(sat)}^*$	$I_C=3A, I_B=60mA$			0.4	V
Transition frequency	$f_T$	$V_{CE}=10V, I_C=50mA$		200		MHz
Collector output capacitance	$C_{ob}$	$V_{CB}=10V, f=1MHz$		30		pF


\*PULSE TEST

## TO-92 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	3.300	3.700	0.130	0.146
A1	1.100	1.400	0.043	0.055
b	0.380	0.550	0.015	0.022
c	0.360	0.510	0.014	0.020
D	4.300	4.700	0.169	0.185
D1	3.430		0.135	
E	4.300	4.700	0.169	0.185
e	1.270 TYP		0.050 TYP	
e1	2.440	2.640	0.096	0.104
L	14.100	14.500	0.555	0.571
Φ		1.600		0.063
h	0.000	0.380	0.000	0.015

## TO-92 Suggested Pad Layout




### Note:

1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.05\text{mm}$ .
3. The pad layout is for reference purposes only.


### NOTICE

JCET reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JCET does not assume any liability arising out of the application or use of any product described herein.

TO-92 PACKAGE TAPEING DIMENSION



Dimiensions are in millimeter								
A1	A	T	P	P0	P2	F1	F2	W
4.5	4.5	3.5	12.7	12.7	6.35	2.5	2.5	18.0
W0	W1	W2	H	H0	D0	t1	t2	ΔP
6.0	9.0	1.0 MAX.	19.0	16.0	4.0	0.4	0.2	0



Package	Box	Box Size(mm)	Carton	Carton Size(mm)
TO-92	2000 pcs	333×162×43	20,000 pcs	350×340×250